

Model 2100TM Drill Rig

- *Telescoping dry kelly. Standard unit has two kellys for drill depths to 60 ft (18.3m)*
- *Available mounted on a three-axle truck or crawler undercarriage*
- *Torque converter drive powershift transmission*
- *Easy set up, highly maneuverable*
- *Hydraulic winches. Inner kelly winch has "controlled freefall"*
- *Weights: Truck rig – 54,220 lb (24,616 kg), Crawler rig – 56,000 lb (25,424 kg)*
- *Capacity - Typical hole diameters: 30 to 54 in (76 to 137 cm), Hole depth: 60 ft (18.3 m)*
- *Performance - Torque: 56,000 lb-ft (76,160 Nm), Hoist: 18,000 lb (80 kN), Crowd: 24,000 lb (107 kN)*



Specifications subject to change.

Our Standard Specifications

EDT-7 ExcaDrill®



CAPACITY

Typical hole diameters:
42 to 54 in (107 to 137 cm)
Drill depth with standard
23 ft 4 in (7.1 m) mast:
86 ft (26.2 m)

PERFORMANCE

Torque:
60,000 lb-ft (81,600 Nm)
Hoist: 25,000 lb (111 kN)
Crowd: 20,000 lb (89 kN)

MOUNTING Excavator weight class: 40 - 45 tons (36 to 41 t)

EDT-10 ExcaDrill®



CAPACITY

Typical hole diameters:
48 to 96 in (122 to 244 cm)
Drill depth with standard
21 ft 0 in (6.4 m) mast:
79 ft (24.1 m)

PERFORMANCE

Torque:
82,000 lb-ft (111,520 Nm)
Hoist: 25,000 lb (111 kN)
Crowd: 23,000 lb (102 kN)

MOUNTING Excavator weight class: 50 tons (45 t)

1100



CAPACITY

Typical hole diameters:
24 to 48 in (60 to 122 cm)
Hole depth: 50 ft (15.2 m)
(Short Mast Option Available)

PERFORMANCE

Torque:
41,600 lb-ft (56,576 Nm)
Hoist: 18,000 lb (80 kN)
Crowd: 23,000 lb (102 kN)

2500



CAPACITY

Typical hole diameters:
36 to 76 in (90 to 193 cm)
Hole depth: 120 ft (36.6 m)

PERFORMANCE

Torque:
81,000 lb-ft (110,160 Nm)
Hoist: 25,000 lb (111 kN)
Crowd: 38,000 lb (169 kN)

3110 Eagle 3100



CAPACITY

Typical hole diameters:
48 to 96 in (122 to 244 cm)
Hole depth: 120 ft (36.6 m)

PERFORMANCE

Torque:
113,000 lb-ft (153,680 Nm)
Hoist: 30,000 lb (134 kN)
Crowd: 50,000 lb (223 kN)

4400



CAPACITY

Typical hole diameters:
48 to 144 in (122 to 366 cm)
Hole depth: 135 ft (41.1 m)
(Hydraulic Rotary)

PERFORMANCE

Torque:
150,000 lb-ft (203,500 Nm)
Hoist: 60,000 lb (267 kN)
Crowd: 60,000 lb (267 kN)

5000CA



CAPACITY

Typical hole diameters:
48 to 96 in (122 to 244 cm)
Hole depth: Variable
depending on kelly
configuration

PERFORMANCE

Torque:
113,000 lb-ft (153,680 Nm)
MOUNTING
Minimum crane capacity:
40 tons (36 t)